

# INK WW 30

---

<b><u>INK WW 30:</u></b>	Economical non-transparent water based acrylic ink with the standard pigments, used mostly for papier cement bags. They can also be used for flexographic printing with or without doctor blade.
<b><u>Usage:</u></b>	different types of paper, carton and card-board, specially recommended for their uncoated varieties.
<b><u>Performance:</u></b>	optimal gloss high resistance to temperature 120-140°C high water resistance after 24h
<b><u>Efficiency:</u></b>	130 m <sup>2</sup> /kg
<b><u>Reaction (pH scale):</u></b>	slightly alkaline: <b>7.8-8.2</b>
<b><u>Package:</u></b>	bucket 20 kg, 30kg or drum 200kg, or IBC 1000kg
<b><u>Additions:</u></b>	WW30-04050 extender for change of shade CA-010558 antifoam max 1% CA-00130 wash cleaner CA-00185 wax max 6% CP-00001 accelerator for ink CW-531184 rub resistance wax CZ-115414 thickeners of ink max 0.5%
<b><u>Thinners:</u></b>	standart thinner: water (optimal 7%) accelerator: ethanol / water (1:1) retarder: CA-00186
<b><u>Anilox:</u></b>	ceramic or chromic cylinder
<b><u>Imrortant:</u></b>	polimers and aniloxes must be cleaned after work. Ink of this type cannot be stored in temperature lower than 5°C
<b><u>Viscosity:</u></b>	26-38 s FORD N°4
<b><u>Warranty:</u></b>	Mix well before use. Ink in its original packaging (20kg lub 30kg), closed and stored in standard conditions has 12 months of usege period. Ink of this type cannot be stored in temperature lower than 5°C.

---

W przypadku pytań proszę o kontakt z "INK Polska": tel. +48 61 8158 500

---